Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name : Oasis clean 32 S

UFI : F4VQ-DRDT-010E-CP1Q

Product code : 114325E

Use of the

Substance/Mixture

Floor Cleaner

Substance type: : Mixture

For professional users only.

Product dilution information : 1.0 % - 3.0 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Floor cleaner. Manual process

Recommended restrictions

on use

: Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Limited

Forest Park

Mullingar Industrial Estate, Mullingar Co. Westmeath Ireland +353

1 276 3500

infoireland@ecolab.com

Ecolab Ltd.

PO Box 11; Winnington Avenue

Northwich, Cheshire, United Kingdom CW8 4DX

+353 (0)1 276 3500 ccs@ecolab.com

1.4 Emergency telephone number

Poison Information Centre

telephone number

Poisons Information: For information or to report a poisoning incident contact The National Poisons Information Centre (01

8092166)

Date of Compilation/Revision : 15.02.2023 Version : 2.2

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

114325E 1 / 18

Classification (REGULATION (EC) No 1272/2008)

Product AS SOLD

Eye irritation, Category 2 H319

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Product AS SOLD

Hazard pictograms

Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**

P280e Wear eye protection/face protection.

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.3 Other hazards

Product AS SOLD

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Product AS SOLD Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Isopropyl Alcohol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336	>= 5 - < 10
Di(2-Ethylhexyl) Sodium Sulfosuccinate	577-11-7 209-406-4 01-2119491296-29	Skin irritation Category 2; H315 Serious eye damage Category 1; H318	>= 1 - < 2.5
Substances with a workp	lace exposure limit:		
ethanol	64-17-5 200-578-6 01-2119457610-43	Flammable liquids Category 2; H225 Serious eye damage/eye irritation Category 2; H319	>= 0.25 - < 0.5

114325E 2 / 18

	Serious eye damage/eye irritation Category 2 50 - 100 %	
--	---	--

Product AT USE DILUTION Hazardous components

Chemical Name	CAS-No.	Classification	Concentration
	EC-No.	REGULATION (EC) No 1272/2008	: [%]
	REACH No.	, , ,	
Substances with a workp	place exposure limit :		
Isopropyl Alcohol	67-63-0	Flammable liquids Category 2; H225	>= 0.25 - <
	200-661-7	Eye irritation Category 2; H319	0.5
	01-2119457558-25	Specific target organ toxicity - single exposure Category 3; H336	

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

Product AS SOLD

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for

at least 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Get medical attention.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

Product AT USE DILUTION

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

114325E 3 / 18

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Fire Hazard

Keep away from heat and sources of ignition. Flash back possible over considerable distance.

Beware of vapours accumulating to form explosive concentrations.

Vapours can accumulate in low areas.

Hazardous combustion

products

: Depending on combustion properties, decomposition products

may include following materials:

Carbon oxides Sulphur oxides metal oxides

5.3 Advice for firefighters

for firefighters

Special protective equipment: Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be

disposed of in accordance with local regulations. In the event of

fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Product AS SOLD

Advice for non-emergency

personnel

: Remove all sources of ignition. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in

sections 7 and 8.

Advice for emergency

responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable

materials.

Product AT USE DILUTION

Advice for non-emergency

personnel

: Refer to protective measures listed in sections 7 and 8.

Advice for emergency

responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable

materials.

6.2 Environmental precautions

Product AS SOLD

: Do not allow contact with soil, surface or ground water. Environmental precautions

Product AT USE DILUTION

Environmental precautions : No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to

114325E 4/18

do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up

: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information. For personal protection see section 8. See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD

Advice on safe handling

: Avoid contact with skin and eyes. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling. Open drum carefully as content may be under pressure. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.

Product AT USE DILUTION

Advice on safe handling

: Wash hands after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE). For personal protection see section 8

Hygiene measures

: Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Product AS SOLD

Requirements for storage areas and containers

: Keep away from heat and sources of ignition. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 40 °C

114325E 5 / 18

Product AT USE DILUTION

Requirements for storage : Keep out of reach of children. Keep container tightly closed. Store

areas and containers in suitable labeled containers.

7.3 Specific end uses

Product AS SOLD

Specific use(s) : Floor cleaner. Manual process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Product AS SOLD

Occupational Exposure Limits

Components	CAS-No.		Value type (Form of exposure)	Control parameters	Basis
Isopropyl Alcohol	67-63-0		OELV - 8 hrs (TWA)	200 ppm	IR_OEL
Further information			ances which have the capacity to penetrate intact skin when they come act with it, and be absorbed into the body		
			OELV - 15 min (STEL)	400 ppm	IR_OEL
Further information	Sk Substances which have the capacity to penetrate intact skin when they com in contact with it, and be absorbed into the body		when they come		
ethanol	64-17-5	j	OELV - 15 min (STEL)	1,000 ppm	IR_OEL

DNEL

End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 500 mg/m3 End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects 319 mg/kg End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 89 mg/m3 End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects 26 mg/kg
End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects

114325E 6 / 18

Value: 175 mg/m3

End Use: Workers **Exposure routes: Dermal**

Potential health effects: Long-term systemic effects

Value: 2750 mg/m3

End Use: Workers Exposure routes: Dermal

Potential health effects: Long-term local effects

Value: 0.132 mg/m3

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 52 mg/m3

End Use: Consumers Exposure routes: Dermal

Potential health effects: Long-term systemic effects

Value: 1650 mg/m3

End Use: Consumers **Exposure routes: Dermal**

Potential health effects: Long-term local effects

Value: 0.079 mg/m3

End Use: Consumers Exposure routes: Oral

Potential health effects: Long-term systemic effects

Value: 15 mg/m3

PNEC

Isopropyl Alcohol	T :	Fresh water
		Value: 140.9 mg/l
		Marine water Value: 140.9 mg/l
		Intermittent use/release Value: 140.9 mg/l
		Fresh water Value: 552 mg/kg
		Marine sediment Value: 552 mg/kg
		Soil Value: 28 mg/kg
		Sewage treatment plant Value: 2251 mg/l
		Oral Value: 160 mg/kg

114325E 7/18

Linear(C12-C14)alkanol,	:	Fresh water
ethoxylated, sulfated, sodium salt		Value: 0.24 mg/l
		Marine water
		Value: 0.024 mg/l
		Sewage treatment plant
		Value: 10000 mg/l
		Fresh water sediment
		Value: 0.917 mg/kg
		Marine sediment
		Value: 0.092 mg/kg
		Soil
		Value: 7.5 mg/kg

8.2 Exposure controls

Product AS SOLD Appropriate engineering controls

Engineering measures : Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

Individual protection measures

: Handle in accordance with good industrial hygiene and safety Hygiene measures

practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

Eye/face protection (EN 166) : Safety glasses with side-shields

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection

(EN 14605)

: No special protective equipment required.

Respiratory protection (EN

143, 14387)

: None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified

respiratory protection equipment meeting EU

requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods

or procedures of work organization.

Product AT USE DILUTION Appropriate engineering controls

Engineering measures : Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

Individual protection measures

114325E 8 / 18

Hygiene measures : Wash hands before breaks and immediately after handling the

product.

Eye/face protection (EN

166)

: No special protective equipment required.

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection

(EN 14605)

: No special protective equipment required.

Respiratory protection (EN

143, 14387)

: None required if airborne concentrations are maintained below the

exposure limit listed in Exposure Limit Information. Use certified

respiratory protection equipment meeting EU

requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods

or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

	Product AS SOLD Product AT USE DIL	UTION
Physical state	liquid liquid	
Colour	purple colourless	
Odour	alcohol-like mild	
рН	6.3 - 7.3, 100 %	
Particle characteristics		
Assessment	not applicable not applicable	
Particle size	not applicable not applicable	
Particle Size Distribution	not applicable not applicable	
Dustiness	not applicable not applicable	
Specific surface area	not applicable not applicable	
Surface charge/Zeta potential	not applicable not applicable	
Shape	not applicable not applicable	
Crystallinity	not applicable not applicable	
Surface treatment /Coatings	not applicable not applicable	
Flash point	38 °C closed cup, Does not sustain combustion.	

: Not applicable and/or not determined for the mixture

: Not applicable and/or not determined for the mixture

: Not applicable and/or not determined for the mixture

114325E 9 / 18

Odour Threshold

Melting point/freezing point

Boiling point, initial boiling

point and boiling range

Evaporation rate : Not applicable and/or not determined for the mixture Flammability : Not applicable and/or not determined for the mixture Upper explosion limit : Not applicable and/or not determined for the mixture Lower explosion limit : Not applicable and/or not determined for the mixture Vapour pressure : Not applicable and/or not determined for the mixture Relative vapour density : Not applicable and/or not determined for the mixture

Density and / or relative : 0.986 - 0.992

density

Water solubility : soluble

Solubility in other solvents : Not applicable and/or not determined for the mixture Partition coefficient: n- : Not applicable and/or not determined for the mixture

octanol/water (log value)

Auto-ignition temperature : Not applicable and/or not determined for the mixture

Thermal decomposition : Not applicable and/or not determined for the mixture

Viscosity, kinematic : Not applicable and/or not determined for the mixture

Explosive properties : Not applicable and/or not determined for the mixture

: The substance or mixture is not classified as oxidizing.

9.2 Other information

Oxidizing properties

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials: Carbon oxides
Sulphur oxides
metal oxides

114325E 10 / 18

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product AS SOLD

exposure

Information on likely routes of : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : There is no data available for this product.

Acute inhalation toxicity : There is no data available for this product.

Acute dermal toxicity : There is no data available for this product.

Skin corrosion/irritation : There is no data available for this product.

Serious eye damage/eye

irritation

: There is no data available for this product.

Respiratory or skin

sensitization

: There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : Isopropyl Alcohol LD50 rat: 5,840 mg/kg

Di(2-Ethylhexyl) Sodium Sulfosuccinate LD50 rat: 3,000 mg/kg

ethanol LD50 rat: 10,470 mg/kg

Components

Acute inhalation toxicity : Isopropyl Alcohol 4 h LC50 rat: > 30 mg/l

Test atmosphere: vapour

ethanol 4 h LC50 rat: 117 mg/l Test atmosphere: vapour

Components

114325E 11 / 18

Acute dermal toxicity : Isopropyl Alcohol LD50 rabbit: 12,870 mg/kg

Di(2-Ethylhexyl) Sodium Sulfosuccinate LD50 rabbit: > 10,000

mg/kg

ethanol LD50 rabbit: 15,800 mg/kg

Potential Health Effects

Product AS SOLD

Eyes : Causes serious eye irritation.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact : Redness, Pain, Irritation

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

Product AT USE DILUTION

Eye contact : No symptoms known or expected.

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

11.2 Information on other hazards

Further information : no data available

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

114325E 12 / 18

Product AS SOLD

Environmental Effects : This product has no known ecotoxicological effects.

Product AT USE DILUTION

Environmental Effects : This product has no known ecotoxicological effects.

Product AS SOLD

Product

Toxicity to fish : no data available Toxicity to daphnia and other : no data available

aquatic invertebrates

Toxicity to algae : no data available

Components

Toxicity to fish : Isopropyl Alcohol

96 h LC50 Pimephales promelas (fathead minnow): 9,640 mg/l

Di(2-Ethylhexyl) Sodium Sulfosuccinate 96 h LC50 Danio rerio (zebra fish): 49 mg/l

ethanol

96 h LC50 Pimephales promelas (fathead minnow): > 100 mg/l

Components

Toxicity to daphnia and other : Isopropyl Alcohol

aquatic invertebrates

LC50 Daphnia magna (Water flea): > 10,000 mg/l

Di(2-Ethylhexyl) Sodium Sulfosuccinate

48 h EC50 Daphnia magna (Water flea): 6.6 mg/l

ethanol

48 h EC50 Aquatic Invertebrate: 857 mg/l

Components

Toxicity to algae : Di(2-Ethylhexyl) Sodium Sulfosuccinate

72 h EC50 Desmodesmus subspicatus (green algae): 82.5 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable

according to the requirements of the detergent regulation

648/2004/EC

Components

Biodegradability : Isopropyl Alcohol

Result: Readily biodegradable.

Di(2-Ethylhexyl) Sodium Sulfosuccinate

Result: Readily biodegradable.

Result: Readily biodegradable.

114325E 13 / 18

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be

either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or

higher.

12.6 Endocrine disrupting properties

no data available

12.7 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD

Product : Where possible recycling is preferred to disposal or incineration. If

recycling is not practicable, dispose of contents/container in accordance with local regulations Dispose of wastes in an

approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken

to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local,

state, and federal regulations.

Guidance for Waste Code

selection

: Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and

assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC)

and local regulations.

Product AT USE DILUTION

Product : Diluted product can be flushed to sanitary sewer if regulations

permit.

Contaminated packaging : Dispose of in accordance with local, state, and federal regulations.

114325E 14 / 18

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number or ID : Not dangerous goods

number

14.2 UN proper shipping : Not dangerous goods

name

14.3 Transport hazard : Not dangerous goods

class(es)

14.4 Packing group14.5 Environmental hazards14.6 Special precautions forNot dangerous goodsNot dangerous goods

user

Air transport (IATA)

14.1 UN number or ID : Not dangerous goods

number

14.2 UN proper shipping : Not dangerous goods

name

14.3 Transport hazard : Not dangerous goods

class(es)

14.4 Packing group14.5 Environmental hazards14.6 Special precautions forNot dangerous goodsNot dangerous goods

user

Sea transport (IMDG/IMO)

14.1 UN number or ID : Not dangerous goods

number

14.2 UN proper shipping : Not dangerous goods

name

14.3 Transport hazard : Not dangerous goods

class(es)

14.4 Packing group14.5 Environmental hazards14.6 Special precautions forNot dangerous goodsNot dangerous goods

ISET

14.7 Maritime transport in : Not dangerous goods

bulk according to IMO

instruments

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents : less than 5 %: Anionic surfactants

Regulation EC 648/2004

Seveso III: Directive : FLAMMABLE LIQUIDS P5c

114325E 15 / 18

2012/18/EU of the European Parliament and of the Council on the control of majoraccident hazards involving dangerous substances.

Lower tier: 5,000 t Upper tier: 50,000 t

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : Safety, Health and Welfare at Work Act, 2005

European Communities (Classification, Packaging, Labelling and Notification of Dangerous Preparations) Regulations 1995. (S.I.

272 of 1995) as amended

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Eye irritation 2, H319	Calculation method

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent,

114325E 16 / 18

Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Floor cleaner. Manual process

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based

products)

Contributing scenario controlling environmental exposure for:

Environmental release : **ERC8a** Wide dispersive indoor use of processing aids in open

systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment : Municipal sewage treatment plant

Plant

category

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and : Indoor

risk management measures

114325E 17 / 18

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/

discharging) from/ to vessels/ large containers at non-

dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures

Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

114325E 18 / 18