

**GREASELIFT****Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : GREASELIFT

Product code : 116864E

Use of the Substance/Mixture : Grill Cleaner

Substance type: : Mixture

**For professional users only.**

Product dilution information : 16.8 %

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Kitchen cleaner. Manual process  
Oven/Grill Cleaner. Manual process  
Oven/Grill Cleaner. Spray and wipe manual process

Recommended restrictions on use : Reserved for industrial and professional use.

**1.3 Details of the supplier of the safety data sheet**

Company : Ecolab Ltd.  
PO Box 11; Winnington Avenue  
Northwich, Cheshire, United Kingdom CW8 4DX  
+ 44 (0)1606 74488  
ccs@ecolab.com

**1.4 Emergency telephone number**

Emergency telephone number : +441618841235  
+32-(0)3-575-5555 Trans-European

Poison Information Centre telephone number : For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 07.11.2022  
Version : 5.0

**Section: 2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)****Product AS SOLD**

|| Acute toxicity, Category 4

H332

**GREASELIFT**

Skin corrosion, Category 1  
 Serious eye damage, Category 1

H314  
 H318

**Product AT USE DILUTION**

Not a hazardous substance or mixture.

**2.2 Label elements**

**Labelling (REGULATION (EC) No 1272/2008)**

**Product AS SOLD**

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H314  
 H332

Causes severe skin burns and eye damage.  
 Harmful if inhaled.

Precautionary Statements

: **Prevention:**  
 P280

Wear protective gloves/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Benzyl alcohol  
 2-butoxyethanol  
 isopropanolamine  
 2-(2-aminoethoxy)ethanol

**Product AT USE DILUTION**

Not a hazardous substance or mixture.

**Additional Labelling:**

**Product AS SOLD**

Special labelling of certain mixtures : Not applicable.

**Product AT USE DILUTION**

Special labelling of certain mixtures : Safety data sheet available on request.

**2.3 Other hazards**

**Product AS SOLD**

None known.

**Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2 Mixtures**

**GREASELIFT****Product AS SOLD  
Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Benzyl alcohol	100-51-6 202-859-9 01-2119492630-38	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Serious eye damage/eye irritation Category 2; H319	>= 30 - < 50
2-butoxyethanol	111-76-2 203-905-0 01-2119475108-36	Acute toxicity Category 4; H302 Acute toxicity Category 3; H331 Skin irritation Category 2; H315 Eye irritation Category 2; H319	>= 5 - < 10
9-octadecenoic acid (z)-, compd. with 2- aminoethanol (1:1)	2272-11-9 218-878-0 01-2119958940-28	Eye irritation Category 2; H319	>= 5 - < 10
Poly(oxy-1,2-ethanediyl), .alpha.-(phenylmethyl)- .omega.-hydroxy-	26403-74-7	Eye irritation Category 2; H319	>= 5 - < 10
isopropanolamine	78-96-6 201-162-7 01-2119475331-43	Skin corrosion Category 1B; H314	>= 5 - < 10
2-(2-aminoethoxy)ethanol	929-06-6 213-195-4 01-2119520701-52	Skin corrosion Sub-category 1B; H314 Serious eye damage Category 1; H318	>= 5 - < 10
Benzenesulfonic acid, C10-16-alkyl derivs., potassium salts	68584-27-0 271-534-1 REACH EXEMPTED	Acute toxicity Category 4; H302 Eye irritation Category 2; H319	>= 2.5 - < 5
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	68891-38-3 500-234-8 01-2119488639-16	Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412  Serious eye damage/eye irritation Category 1 10 - 100 % Serious eye damage/eye irritation Category 2A > 5 - < 10 %	>= 3 - < 5
monoethanolamine	141-43-5 205-483-3 01-2119486455-28	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Sub-category 1B; H314 Chronic aquatic toxicity Category 3; H412 Specific target organ toxicity - single exposure Category 3; H335  Specific target organ toxicity - single exposure Category 3 H335 5 - 100 %	>= 3 - < 5
Amines, C12-14 alkyldimethyl, N-oxides	308062-28-4 01-2119490061-47	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 2; H411	>= 0.5 - < 1

**GREASELIFT**

M = 1

**Product AT USE DILUTION  
Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Benzyl alcohol	100-51-6 202-859-9 01-2119492630-38	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Serious eye damage/eye irritation Category 2; H319	>= 5 - < 10
2-butoxyethanol	111-76-2 203-905-0 01-2119475108-36	Acute toxicity Category 4; H302 Acute toxicity Category 3; H331 Skin irritation Category 2; H315 Eye irritation Category 2; H319	>= 1 - < 2.5
9-octadecenoic acid (z)-, compd. with 2- aminoethanol (1:1)	2272-11-9 218-878-0 01-2119958940-28	Eye irritation Category 2; H319	>= 1 - < 2.5
Dodecyldimethylamine oxide	1643-20-5 216-700-6 01-2120068065-58	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 2; H411	>= 0.1 - < 0.25
<b>Substances with a workplace exposure limit :</b>			
monoethanolamine	141-43-5 205-483-3 01-2119486455-28	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Sub-category 1B; H314 Chronic aquatic toxicity Category 3; H412 Specific target organ toxicity - single exposure Category 3; H335  Specific target organ toxicity - single exposure Category 3 H335 5 - 100 %	>= 0.5 - < 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

**Section: 4. FIRST AID MEASURES****4.1 Description of first aid measures****Product AS SOLD**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**GREASELIFT**

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention.

**Product AT USE DILUTION**

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

**4.2 Most important symptoms and effects, both acute and delayed**

See Section 11 for more detailed information on health effects and symptoms.

**4.3 Indication of immediate medical attention and special treatment needed**

Treatment : Treat symptomatically.

**Section: 5. FIREFIGHTING MEASURES**

**Product AS SOLD**

**5.1 Extinguishing media**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:  
Carbon oxides  
nitrogen oxides (NOx)  
Sulphur oxides  
metal oxides

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

**Section: 6. ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

**Product AS SOLD**

**GREASELIFT**

Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

**Product AT USE DILUTION**

Advice for non-emergency personnel : Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

**6.2 Environmental precautions**

**Product AS SOLD**

Environmental precautions : Do not allow contact with soil, surface or ground water.

**Product AT USE DILUTION**

Environmental precautions : No special environmental precautions required.

**6.3 Methods and materials for containment and cleaning up**

**Product AS SOLD**

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

**Product AT USE DILUTION**

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

**6.4 Reference to other sections**

See Section 1 for emergency contact information.  
For personal protection see section 8.  
See Section 13 for additional waste treatment information.

**Section: 7. HANDLING AND STORAGE**

**7.1 Precautions for safe handling**

**Product AS SOLD**

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal

**GREASELIFT**

Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

**Product AT USE DILUTION**

Advice on safe handling : Wash hands after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE). For personal protection see section 8.

Hygiene measures : Wash hands before breaks and immediately after handling the product.

**7.2 Conditions for safe storage, including any incompatibilities**

**Product AS SOLD**

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 5 °C to 40 °C

**Product AT USE DILUTION**

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

**7.3 Specific end uses**

**Product AS SOLD**

**Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters**

**Product AS SOLD**

**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethanol	111-76-2	TWA	25 ppm 123 mg/m <sup>3</sup>	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	50 ppm 246 mg/m <sup>3</sup>	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	20 ppm 98 mg/m <sup>3</sup>	2000/39/EC
Further information	skin	Identifies the possibility of significant uptake through the skin		
		Indicative		
		STEL	50 ppm 246 mg/m <sup>3</sup>	2000/39/EC
Further information	skin	Identifies the possibility of significant uptake through the skin		
		Indicative		
monoethanolamine	141-43-5	TWA	1 ppm 2.5 mg/m <sup>3</sup>	UKCOSSTD

**GREASELIFT**

Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	3 ppm 7.6 mg/m3	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	1 ppm 2.5 mg/m3	2006/15/EC
Further information		Indicative		
	skin	Identifies the possibility of significant uptake through the skin		
		STEL	3 ppm 7.6 mg/m3	2006/15/EC
Further information		Indicative		
	skin	Identifies the possibility of significant uptake through the skin		

**Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

**DNEL**

triethanolamine	:	<p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 1 mg/m3</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3</p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 7.5 mg/cm2</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 1.25 mg/m3</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1.25 mg/m3</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 3.1 mg/cm2</p> <p>End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 13 ppm</p>
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	:	<p>End Use: Workers Exposure routes: Inhalation</p>



**GREASELIFT**

	<p>Potential health effects: Long-term systemic effects Value: 175 mg/m3</p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 2750 mg/m3</p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.132 mg/m3</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 52 mg/m3</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 1650 mg/m3</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.079 mg/m3</p> <p>End Use: Consumers Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 15 mg/m3</p>
--	--

**PNEC**

<p>triethanolamine</p>	<p>: Fresh water Value: 0.32 mg/l</p> <p>Marine water Value: 0.032 mg/l</p> <p>Intermittent use/release Value: 5.12 mg/l</p> <p>Fresh water sediment Value: 1.7 mg/kg</p> <p>Marine sediment Value: 1.7 mg/kg</p> <p>Sewage treatment plant Value: 10 mg/l</p> <p>Soil Value: 0.151 mg/kg</p>
<p>Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium</p>	<p>: Fresh water</p>

**GREASELIFT**

salt	Value: 0.24 mg/l  Marine water Value: 0.024 mg/l  Sewage treatment plant Value: 10000 mg/l  Fresh water sediment Value: 0.917 mg/kg  Marine sediment Value: 0.092 mg/kg  Soil Value: 7.5 mg/kg
------	---

**8.2 Exposure controls**

**Product AS SOLD**

**Appropriate engineering controls**

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

**Individual protection measures**

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles  
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection  
Gloves  
Nitrile rubber  
butyl-rubber  
Breakthrough time: 1 – 4 hours  
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods

**GREASELIFT**

or procedures of work organization.

**Product AT USE DILUTION**

**Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Individual protection measures**

Hygiene measures : Wash hands before breaks and immediately after handling the product.

Eye/face protection (EN 166) : No special protective equipment required.

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

**Environmental exposure controls**

General advice : Consider the provision of containment around storage vessels.

**Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties**

	<b>Product AS SOLD</b>	<b>Product AT USE DILUTION</b>
Appearance	: liquid	liquid
Colour	: clear, orange	light orange
Odour	: slight	slight
pH	: 10.5 - 11.5, 100 %	10.1 - 10.9
Flash point	: 96 °C closed cup, Does not sustain combustion.	
Odour Threshold	: Not applicable and/or not determined for the mixture	
Melting point/freezing point	: Not applicable and/or not determined for the mixture	
Initial boiling point and boiling range	: > 100 °C	
Evaporation rate	: Not applicable and/or not determined for the mixture	
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture	
Upper explosion limit	: Not applicable and/or not determined for the mixture	
Lower explosion limit	: Not applicable and/or not determined for the mixture	
Vapour pressure	: Not applicable and/or not determined for the mixture	

**GREASELIFT**

Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 1.04 - 1.06
Water solubility	: Not applicable and/or not determined for the mixture
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

**9.2 Other information**

Not applicable and/or not determined for the mixture

**Section: 10. STABILITY AND REACTIVITY**

**Product AS SOLD**

**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

No dangerous reaction known under conditions of normal use.

**10.4 Conditions to avoid**

None known.

**10.5 Incompatible materials**

Acids  
Metals

**10.6 Hazardous decomposition products**

Depending on combustion properties, decomposition products may include following materials:

Carbon oxides  
nitrogen oxides (NOx)  
Sulphur oxides  
metal oxides

**Section: 11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Product AS SOLD**

**GREASELIFT**

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

**Product**

- Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg
- Acute inhalation toxicity : 4 h Acute toxicity estimate : 1.96 mg/l  
Test atmosphere: dust/mist
- Acute dermal toxicity : Acute toxicity estimate : > 2,000 mg/kg
- Skin corrosion/irritation : There is no data available for this product.
- Serious eye damage/eye irritation : There is no data available for this product.
- Respiratory or skin sensitization : There is no data available for this product.
- Carcinogenicity : There is no data available for this product.
- Reproductive effects : There is no data available for this product.
- Germ cell mutagenicity : There is no data available for this product.
- Teratogenicity : There is no data available for this product.
- STOT - single exposure : The substance or mixture is not classified as specific target organ toxicant, single exposure.
- STOT - repeated exposure : There is no data available for this product.
- Aspiration toxicity : There is no data available for this product.

**Components**

- Acute oral toxicity : Benzyl alcohol LD50 rat: 1,620 mg/kg
- 2-butoxyethanol LD50 rat: 1,500 mg/kg
- 9-octadecenoic acid (z)-, compd. with 2-aminoethanol (1:1) LD50 rat: > 2,000 mg/kg
- Poly(oxy-1,2-ethanediyl), .alpha.-(phenylmethyl)-.omega.-hydroxy-LD50 rat: > 2,000 mg/kg
- isopropanolamine LD50 rat: > 2,000 mg/kg
- 2-(2-aminoethoxy)ethanol LD50 rat: 3,400 mg/kg
- Benzenesulfonic acid, C10-16-alkyl derivs., potassium salts LD50 rat: 1,249 mg/kg
- Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt LD50 rat: 3,350 mg/kg
- monoethanolamine LD50 rat: 1,089 mg/kg
- Amines, C12-14 alkyldimethyl, N-oxides LD50 rat: 1,064 mg/kg

**GREASELIFT**

**Components**

Acute inhalation toxicity : isopropanolamine 4 h LC50 rat: > 5.19 mg/l  
Test atmosphere: dust/mist

Benzenesulfonic acid, C10-16-alkyl derivs., potassium salts 4 h  
LC50 rat: > 1.9 mg/l  
Test atmosphere: dust/mist

monoethanolamine 4 h LC50 rat: > 1.6 mg/l  
Test atmosphere: dust/mist

**Components**

Acute dermal toxicity : 9-octadecenoic acid (z)-, compd. with 2-aminoethanol (1:1) LD50  
rabbit: > 2,000 mg/kg

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt LD50  
rat: 8,000 mg/kg

monoethanolamine LD50 rabbit: 1,025 mg/kg

**Potential Health Effects**

**Product AS SOLD**

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : Harmful if inhaled. May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

**Product AT USE DILUTION**

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

**Experience with human exposure**

**Product AS SOLD**

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

**Product AT USE DILUTION**

Eye contact : No symptoms known or expected.

**GREASELIFT**

Skin contact : No symptoms known or expected.  
 Ingestion : No symptoms known or expected.  
 Inhalation : No symptoms known or expected.

**Section: 12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

**Product AS SOLD**

Environmental Effects : This product has no known ecotoxicological effects.

**Product AT USE DILUTION**

Environmental Effects : This product has no known ecotoxicological effects.

**Product AS SOLD  
Product**

Toxicity to fish : no data available  
 Toxicity to daphnia and other aquatic invertebrates : no data available  
 Toxicity to algae : no data available

**Components**

Toxicity to fish : Benzyl alcohol 96 h LC50 Pimephales promelas (fathead minnow): 460 mg/l  
 2-butoxyethanol 96 h LC50 Fish: > 100 mg/l  
 9-octadecenoic acid (z)-, compd. with 2-aminoethanol (1:1) 96 h LC50 Fish: 7.44 mg/l  
 Poly(oxy-1,2-ethanediyl), .alpha.-(phenylmethyl)-.omega.-hydroxy- 96 h LC50: > 100 mg/l  
 2-(2-aminoethoxy)ethanol 96 h LC50 Leuciscus idus (Golden orfe): 460 mg/l  
 Benzenesulfonic acid, C10-16-alkyl derivs., potassium salts 96 h LC50 Fish: 5.07 mg/l  
 Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt 96 h LC50 Danio rerio (zebra fish): 7.1 mg/l  
 Amines, C12-14 alkyldimethyl, N-oxides 96 h LC50: 2.67 mg/l

**Components**

Toxicity to daphnia and other aquatic invertebrates : Benzyl alcohol 48 h EC50 Daphnia magna (Water flea): 230 mg/l  
 2-(2-aminoethoxy)ethanol 48 h EC50 Daphnia magna (Water flea): 189 mg/l  
 Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt 48 h EC50 Daphnia magna (Water flea): 7.4 mg/l

**GREASELIFT**

monoethanolamine 48 h LC50 Daphnia magna (Water flea): 65 mg/l

Amines, C12-14 alkyldimethyl, N-oxides 48 h EC50 Daphnia magna (Water flea): 3.1 mg/l

**Components**

Toxicity to algae

: Benzyl alcohol 72 h EC50 Pseudokirchneriella subcapitata (green algae): 770 mg/l

2-butoxyethanol 72 h EC50 Aquatic Plant: 911 mg/l

isopropanolamine 72 h EC50: 32.7 mg/l

2-(2-aminoethoxy)ethanol 72 h EC50 Desmodesmus subspicatus (green algae): 202 mg/l

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt 72 h EC50 Desmodesmus subspicatus (green algae): 27.7 mg/l

Amines, C12-14 alkyldimethyl, N-oxides 72 h LC50: 0.143 mg/l  
72 h NOEC: 0.067 mg/l

**12.2 Persistence and degradability**

**Product**

Biodegradability

: The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

**Components**

Biodegradability

: Benzyl alcohol Result: Readily biodegradable.

2-butoxyethanol Result: Readily biodegradable.

9-octadecenoic acid (z)-, compd. with 2-aminoethanol (1:1) Result: Readily biodegradable.

Poly(oxy-1,2-ethanediyl), .alpha.-(phenylmethyl)-.omega.-hydroxy- Result: Readily biodegradable.

isopropanolamine Result: Readily biodegradable.

2-(2-aminoethoxy)ethanol Result: Biodegradable

Benzenesulfonic acid, C10-16-alkyl derivs., potassium salts Result: Readily biodegradable.

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt Result: Readily biodegradable.

monoethanolamine Result: Readily biodegradable.

Amines, C12-14 alkyldimethyl, N-oxides Result: Readily biodegradable.



**GREASELIFT**

**12.3 Bioaccumulative potential**

no data available

**12.4 Mobility in soil**

no data available

**12.5 Results of PBT and vPvB assessment**

**Product**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects**

no data available

**Section: 13. DISPOSAL CONSIDERATIONS**

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

**13.1 Waste treatment methods**

**Product AS SOLD**

Product : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

**Product AT USE DILUTION**

Product : Diluted product can be flushed to sanitary sewer if regulations permit.

Contaminated packaging : Dispose of in accordance with local, state, and federal regulations.

**Section: 14. TRANSPORT INFORMATION**

**GREASELIFT**

**Product AS SOLD**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

**Land transport (ADR/ADN/RID)**

14.1 UN number : 3267  
14.2 UN proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.  
(2-(2-aminoethoxy)ethanol, isopropanolamine)  
14.3 Transport hazard class(es) : 8  
14.4 Packing group : III  
14.5 Environmental hazards : No  
14.6 Special precautions for user : None

**Air transport (IATA)**

14.1 UN number : 3267  
14.2 UN proper shipping name : Corrosive liquid, basic, organic, n.o.s.  
(2-(2-aminoethoxy)ethanol, isopropanolamine)  
14.3 Transport hazard class(es) : 8  
14.4 Packing group : III  
14.5 Environmental hazards : No  
14.6 Special precautions for user : None

**Sea transport (IMDG/IMO)**

14.1 UN number : 3267  
14.2 UN proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.  
(2-(2-aminoethoxy)ethanol, isopropanolamine)  
14.3 Transport hazard class(es) : 8  
14.4 Packing group : III  
14.5 Environmental hazards : No  
14.6 Special precautions for user : None  
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

**Section: 15. REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

according to Detergents Regulation EC 648/2004 : 5 % or over but less than 15 %: Anionic surfactants, Soap  
less than 5 %: Non-ionic surfactants  
Other constituents: Perfumes  
Allergens:  
Benzyl alcohol  
  
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major- : Not applicable.

**GREASELIFT**

accident hazards involving dangerous substances.

Candidate List of Substances : Not applicable.  
of Very High Concern for Authorisation

**National Regulations**

**Take note of Dir 94/33/EC on the protection of young people at work.**

Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations.  
The Control of Substances Hazardous to Health Regulations.  
Health and Safety at Work Act.

**15.2 Chemical Safety Assessment**

No Chemical Safety Assessment has been carried out on the product.

**Section: 16. OTHER INFORMATION**

**Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
Acute toxicity 4, H332	Calculation method
Skin corrosion 1, H314	Based on product data or assessment
Serious eye damage 1, H318	Based on product data or assessment

**Full text of H-Statements**

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H400 Very toxic to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

**Full text of other abbreviations**

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing

**GREASELIFT**

Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Annex: Exposure Scenarios**

**Exposure Scenario: Oven/Grill Cleaner. Manual process**

Life Cycle Stage : Widespread use by professional workers  
Product category : **PC35** Washing and cleaning products (including solvent based products)

**Contributing scenario controlling environmental exposure for:**

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems  
Daily amount per site : 7.5 kg  
Type of Sewage Treatment Plant : Municipal sewage treatment plant

**Contributing scenario controlling worker exposure for:**

**GREASELIFT**

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Respiratory Protection : see section 8

Skin Protection : see section 8

**Exposure Scenario: Oven/Grill Cleaner. Spray and wipe manual process**

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

**Contributing scenario controlling environmental exposure for:**

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

**Contributing scenario controlling worker exposure for:**

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Respiratory Protection : see section 8

Skin Protection : see section 8

**Contributing scenario controlling worker exposure for:**

Process category : **PROC11** Non industrial spraying

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

**GREASELIFT**

Local Exhaust Ventilation is not required

General ventilation                      Ventilation rate per hour                      1

Skin Protection                      :    see section 8

Respiratory Protection                      :    see section 8

**Exposure Scenario: Kitchen cleaner. Manual process**

Life Cycle Stage                      :    Widespread use by professional workers

Product category                      :    **PC35**            Washing and cleaning products (including solvent based products)

**Contributing scenario controlling environmental exposure for:**

Environmental release category                      :    **ERC8a**            Wide dispersive indoor use of processing aids in open systems

Daily amount per site                      :    7.5 kg

Type of Sewage Treatment Plant                      :    Municipal sewage treatment plant

**Contributing scenario controlling worker exposure for:**

Process category                      :    **PROC10**            Roller application or brushing

Exposure duration                      :    480 min

Operational conditions and risk management measures                      :    Indoor

Local Exhaust Ventilation is not required

General ventilation                      Ventilation rate per hour                      1

Skin Protection                      :    see section 8

Respiratory Protection                      :    see section 8

**Contributing scenario controlling worker exposure for:**

Process category                      :    **PROC8a**            Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration                      :    60 min

Operational conditions and risk management measures                      :    Indoor

Local Exhaust Ventilation is not required

General ventilation                      Ventilation rate per hour                      1

Skin Protection                      :    see section 8

**GREASELIFT**

Respiratory Protection : see section 8

**Exposure Scenario: Kitchen cleaner. Manual process**

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

**Contributing scenario controlling environmental exposure for:**

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

**Contributing scenario controlling worker exposure for:**

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

**Contributing scenario controlling worker exposure for:**

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8