

**Sirafan Speed****Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : Sirafan Speed  
UFI : CMTE-UCRW-100X-1WCC  
Product code : 110660E  
Use of the Substance/Mixture : Disinfectant  
Substance type: : Mixture

**For professional users only.**

Product dilution information : No dilution information provided.

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Surface disinfectant. Manual process  
Disinfection product. Semi-automatic process  
Recommended restrictions : Reserved for industrial and professional use.  
on use

**1.3 Details of the supplier of the safety data sheet**

Company : Ecolab Deutschland GmbH  
Ecolab-Allee 1  
40789 Monheim am Rhein, Germany +49 (0)2173 599 0  
OfficeService.DEDUS@ecolab.com

**1.4 Emergency telephone number**

Emergency telephone number : +32-(0)3-575-5555 Trans-european, German speaking, 24/7  
or +49 32 212249407 German speaking, 24/7  
Poison Information Centre : +49 (0)551 38318854  
telephone number

Date of Compilation/Revision : 30.01.2023  
Version : 1.14

**Section: 2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 3 H226  
Eye irritation, Category 2 H319

**Sirafan Speed**

Specific target organ toxicity - single exposure, Category 3, H336  
Central Nervous System

The classification of this product is based on toxicological assessment.

**2.2 Label elements**

**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280e Wear eye protection/face protection.

Hazardous components which must be listed on the label:  
Isopropyl Alcohol  
propan-1-ol

**2.3 Other hazards**

None known.

**Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2 Mixtures**

**Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Isopropyl Alcohol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336	>= 30 - < 50
propan-1-ol	71-23-8 200-746-9 01-2119486761-29	Flammable liquids Category 2; H225 Serious eye damage Category 1; H318 Specific target organ toxicity - single exposure Category 3; H336	>= 20 - < 25

For the full text of the H-Statements mentioned in this Section, see Section 16.

**Section: 4. FIRST AID MEASURES**

**4.1 Description of first aid measures**

**Sirafan Speed**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
- In case of skin contact : Rinse with plenty of water.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

**4.2 Most important symptoms and effects, both acute and delayed**

See Section 11 for more detailed information on health effects and symptoms.

**4.3 Indication of immediate medical attention and special treatment needed**

- Treatment : Treat symptomatically.

**Section: 5. FIREFIGHTING MEASURES**

**5.1 Extinguishing media**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : High volume water jet

**5.2 Special hazards arising from the substance or mixture**

- Specific hazards during firefighting : Fire Hazard  
Keep away from heat and sources of ignition.  
Flash back possible over considerable distance.  
Beware of vapours accumulating to form explosive concentrations.  
Vapours can accumulate in low areas.
- Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:  
Carbon oxides

**5.3 Advice for firefighters**

- Special protective equipment for firefighters : Use personal protective equipment.
- Further information : Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

**Section: 6. ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

- Advice for non-emergency personnel : Remove all sources of ignition. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

## Sirafan Speed

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

### 6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
For personal protection see section 8.  
See Section 13 for additional waste treatment information.

## Section: 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling. Open drum carefully as content may be under pressure. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 25 °C

### 7.3 Specific end uses

Specific use(s) : Surface disinfectant. Manual process  
Disinfection product. Semi-automatic process

## Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Sirafan Speed**

**8.1 Control parameters**

**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Isopropyl Alcohol	67-63-0	AGW	200 ppm 500 mg/m3	TRGS 900
Further information	Y	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		

**Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Isopropyl Alcohol	67-63-0	Acetone: 25 mg/l (Blood)	Immediately after exposition or after working hours	TRGS 903
		Acetone: 25 mg/l (Urine)	Immediately after exposition or after working hours	TRGS 903

**DNEL**

Isopropyl Alcohol	:	<p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects 888 mg/kg</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 500 mg/m3</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects 319 mg/kg</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 89 mg/m3</p> <p>End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects 26 mg/kg</p>
Propylene glycol	:	<p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 168 mg/m3</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m3</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 50 mg/m3</p>

**Sirafan Speed**

	<p>End Use: Consumers                  Exposure routes: Inhalation                  Potential health effects: Long-term local effects                  Value: 10 mg/m<sup>3</sup></p> <p>End Use: Consumers                  Exposure routes: Dermal                  Potential health effects: Long-term systemic effects                  213 mg/kg</p> <p>End Use: Consumers                  Exposure routes: Ingestion                  Potential health effects: Long-term systemic effects                  Value: 85 ppm</p>
--	--

**PNEC**

<p>Isopropyl Alcohol</p>	<p>: Fresh water                  Value: 140.9 mg/l</p> <p>Marine water                  Value: 140.9 mg/l</p> <p>Intermittent use/release                  Value: 140.9 mg/l</p> <p>Fresh water                  Value: 552 mg/kg</p> <p>Marine sediment                  Value: 552 mg/kg</p> <p>Soil                  Value: 28 mg/kg</p> <p>Sewage treatment plant                  Value: 2251 mg/l</p> <p>Oral                  Value: 160 mg/kg</p>
<p>Propylene glycol</p>	<p>: Fresh water                  Value: 260 mg/l</p> <p>Marine water                  Value: 26 mg/l</p> <p>Intermittent use/release                  Value: 183 mg/l</p> <p>Fresh water sediment                  Value: 572 mg/kg</p> <p>Marine sediment                  Value: 57.2 mg/kg</p> <p>Sewage treatment plant</p>

**Sirafan Speed**

	Value: 20000 mg/l
	Soil Value: 50 mg/kg

**8.2 Exposure controls**

**Appropriate engineering controls**

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

**Individual protection measures**

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.

Eye/face protection (EN 166) : Safety glasses with side-shields

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:A

**Environmental exposure controls**

General advice : Consider the provision of containment around storage vessels.

**Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties**

Physical state	: liquid
Colour	: colourless
Odour	: alcohol-like
pH	: 7.5 - 8.5, 100 %
Particle characteristics	
Assessment	: not applicable
Particle size	: not applicable
Particle Size Distribution	: not applicable
Dustiness	: not applicable
Specific surface area	: not applicable
Surface charge/Zeta potential	: not applicable

**Sirafan Speed**

Shape	: not applicable
Crystallinity	: not applicable
Surface treatment /Coatings	: not applicable
Flash point	: 25 °C closed cup
Odour Threshold	: Not applicable and/or not determined for the mixture
Melting point/freezing point	: Not applicable and/or not determined for the mixture
Boiling point, initial boiling point and boiling range	: Not applicable and/or not determined for the mixture
Evaporation rate	: Not applicable and/or not determined for the mixture
Flammability	: Not applicable and/or not determined for the mixture
Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Density and / or relative density	: 0.876 - 0.896
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water (log value)	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

**9.2 Other information**

Not applicable and/or not determined for the mixture

**Section: 10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

No dangerous reaction known under conditions of normal use.

**10.4 Conditions to avoid**



## Sirafan Speed

Heat, flames and sparks.

### 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:  
Carbon oxides

## Section: 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

#### Product

Acute oral toxicity : There is no data available for this product.

Acute inhalation toxicity : There is no data available for this product.

Acute dermal toxicity : There is no data available for this product.

Skin corrosion/irritation : No skin irritation

Serious eye damage/eye irritation : Eye irritation  
Method: OECD Test Guideline 405  
Test substance: Similar Product

Respiratory or skin sensitization : There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : May cause drowsiness or dizziness.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

#### Components

Acute oral toxicity : Isopropyl Alcohol LD50 rat: 5,840 mg/kg  
propan-1-ol LD50 : 1,870 mg/kg

#### Components

Acute inhalation toxicity : Isopropyl Alcohol 4 h LC50 rat: > 30 mg/l  
Test atmosphere: vapour

**Sirafan Speed**

propan-1-ol 4 h LC50 : 26.76 mg/l  
Test atmosphere: dust/mist

**Components**

Acute dermal toxicity : Isopropyl Alcohol LD50 rabbit: 12,870 mg/kg  
propan-1-ol LD50 : 4,032 mg/kg

**Potential Health Effects**

Eyes : Causes serious eye irritation.  
Skin : Health injuries are not known or expected under normal use.  
Ingestion : Health injuries are not known or expected under normal use.  
Inhalation : Inhalation may cause central nervous system effects.  
Chronic Exposure : Health injuries are not known or expected under normal use.

**Experience with human exposure**

Eye contact : Redness, Pain, Irritation  
Skin contact : No symptoms known or expected.  
Ingestion : No symptoms known or expected.  
Inhalation : Dizziness, Drowsiness

**11.2 Information on other hazards**

**Further information** : no data available

**Section: 12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

Environmental Effects : This product has no known ecotoxicological effects.

**Product**

Toxicity to fish : no data available  
Toxicity to daphnia and other aquatic invertebrates : no data available  
Toxicity to algae : no data available

**Components**

Toxicity to fish : Isopropyl Alcohol  
96 h LC50 Pimephales promelas (fathead minnow): 9,640 mg/l  
propan-1-ol  
96 h EC50: 3,800 mg/l

**Components**

Toxicity to daphnia and other : Isopropyl Alcohol

## Sirafan Speed

aquatic invertebrates LC50 Daphnia magna (Water flea): > 10,000 mg/l

propan-1-ol  
48 h LC50: 1,000 mg/l

### Components

Toxicity to algae : propan-1-ol  
48 h EC50: 9,170 mg/l

## 12.2 Persistence and degradability

### Product

no data available

### Components

Biodegradability : Isopropyl Alcohol  
Result: Readily biodegradable.

propan-1-ol  
Result: Readily biodegradable.

## 12.3 Bioaccumulative potential

no data available

## 12.4 Mobility in soil

no data available

## 12.5 Results of PBT and vPvB assessment

### Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

## 12.7 Other adverse effects

no data available

## Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

### 13.1 Waste treatment methods

Product : Where possible recycling is preferred to disposal or incineration. If

**Sirafan Speed**

recycling is not practicable, dispose of contents/container in accordance with local regulations Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

**Section: 14. TRANSPORT INFORMATION**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

**Land transport (ADR/ADN/RID)**

14.1 UN number or ID number : 1987  
14.2 UN proper shipping name : ALCOHOLS, N.O.S.  
(Isopropanol, Propanol)  
14.3 Transport hazard class(es) : 3  
14.4 Packing group : III  
14.5 Environmental hazards : No  
14.6 Special precautions for user : None

**Air transport (IATA)**

14.1 UN number or ID number : 1987  
14.2 UN proper shipping name : Alcohols, n.o.s.  
(Isopropanol, Propanol)  
14.3 Transport hazard class(es) : 3  
14.4 Packing group : III  
14.5 Environmental hazards : No  
14.6 Special precautions for user : None

**Sea transport (IMDG/IMO)**

14.1 UN number or ID number : 1987  
14.2 UN proper shipping name : ALCOHOLS, N.O.S.  
(Isopropanol, Propanol)  
14.3 Transport hazard class(es) : 3  
14.4 Packing group : III

**Sirafan Speed**

- 14.5 Environmental hazards : No
- 14.6 Special precautions for user : None
- 14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

**Section: 15. REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances : FLAMMABLE LIQUIDS P5c  
Lower tier : 5,000 t  
Upper tier : 50,000 t

**National Regulations**

**Take note of Dir 94/33/EC on the protection of young people at work.**

- Hazard class for water : WGK 1  
Classification according to AwSV, Annex 1

- German storage class : 3

**15.2 Chemical Safety Assessment**

No Chemical Safety Assessment has been carried out on the product.

**Section: 16. OTHER INFORMATION**

**Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
Flammable liquids 3, H226	Based on product data or assessment
Eye irritation 2, H319	Based on product data or assessment
Specific target organ toxicity - single exposure 3, H336	Based on product data or assessment

**Full text of H-Statements**

- H225 Highly flammable liquid and vapour.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

**Full text of other abbreviations**

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada);

**Sirafan Speed**

ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Annex: Exposure Scenarios**